

Stone Age Concrete Games, Inc.
ADA Waterfall Concrete Foosball Table
Installation Instructions



Specified Installation:

1-piece table. Sets in place with equipment and straps. No assembly required. Bolt down brackets and hardware included.

Size:

55" x 32" x 36"H

Weight:

Approximate weight is 1,100 lb

Concrete:

Table and legs are pre cast 6000+ PSI concrete with steel reinforcement and Novamesh™ fiber reinforcement.

Connectors:

3/8" black anodized button head bolts

Recommended Maximum Loads:

Table top 100psf live load, 420 lb point load

Threaded Inserts:

All bolt connections use Zamac (rustproof) cast in place threaded anchors.

Legs:

6000 psi Concrete reinforced with #4 (1/2") rebar and 15 lb per yard FORTA FERRO™ fiber reinforcement.

Table Tops:

Solid 6000psi+ Concrete. Top is reinforced with 4-4-4-4 welded wire reinforcing steel and 15 pounds per yard Novamesh™ fiber reinforcement. Concrete tops are integrally dyed concrete and or acid stained concrete depending on color selections. Colored tops have some color variation. Standard finish is precision cast and polished finish (similar to smooth solid surface concrete counter top.) Edges are cast 1/4" Chamfer for incidental contact safety.

Foosball Hardware:

Tables use standard size solid stainless steel foosball rods and standard foosball men and handles.

Control Document Revision Date May 5, 2025 AJ