

Stone Age Concrete Games, Inc.

4-Way Round Table Tennis Table

Proprietary

Specified Installation: Bolts together with standard hand tools and supplied vandal resistant fasteners. Table installs quickly on flat hard surface such as concrete and asphalt without sub grade construction. Grass installations require compacted gravel footers below legs. Installation time is approximately 1-2 hours.

Size: 9' (108") diameter x 30" high

Weight: Approximate weight is 4,500 lbs

Concrete: Table and legs are pre cast 5000 PSI concrete with steel reinforcement and FORTA FERRO™ fiber reinforcement.

Connectors: All exposed connectors are pin in hex vandal resistant bolts

Recommended Maximum Loads: Table top 100psf live load, 420 lb point load

Threaded Inserts: All bolt connections use Zamac (rustproof) cast in place threaded anchors.

Legs: 5000 psi Concrete reinforced with #4 (1/2") rebar and 15 lb per yard FORTA FERRO™ fiber reinforcement.

Table Tops: 2 5/8" thick solid 5000psi Concrete. Top is reinforced with 4-4-4-4 welded wire reinforcing steel and 15 pounds per yard FORTA FERRO™ fiber reinforcement. Fiber is installed in backer layer and does not show in the colored polished top. Concrete tops are integrally died concrete. Integrally colored tops have some color variation. Standard finish is precision cast and polished finish (similar to smooth solid surface concrete counter top.) Edges are cast 3/8" radius for incidental contact safety.

Standard Net: Net is 3/8" steel with powder coat finish. (custom design and color options come with the table)(x4)

Option: Custom Stainless Steel Net: 3/8" steel polished and clear powder coat finish.

Steel Runners: Steel runners are 2x2" square 1/8" wall tubing with black powder coating.

Sealer: All concrete parts are sealed with concrete sealer.